

SKID STEERS

■ 2044 ■



mustangmfg.com

PREPARE to dig, load and haul



- Operating capacity of 1,550 lbs. with optional counterweight provides exceptional lifting and loading capabilities.

- Optional sound package lowers noise levels, making a day in the cab more comfortable.



- Maintenance is made easy with a tilt-back ROPS/FOPS structure and two hinged doors on the rear providing access to the engine, control valve and cooling system.

- Offset load-arm design creates a wider operator's compartment, and an optional suspension seat adds even more comfort.



West Bend, WI USA
Tel: 262-334-9461
Fax: 262-338-7517

For more information on Mustang equipment, call our

literature hotline at
800-628-0491

or visit our website:
mustangmfg.com

A Per SAE J818, SAE J732, and ISO 14397
B Unit weight with standard bucket, 175 lbs.
(79 kg) operator and full fuel tank

SPECIFICATIONS

		2044
DIMENSIONS	A. Overall Operating Height - Fully Raised (mm)	143.5" (3645)
	B. Height to Hinge Pin - Fully Raised (mm)	112" (2845)
	C. Overall Height to Top of ROPS (mm)	77.7" (1973)
	D. Ground Clearance to Chassis (mm)	7.5" (191)
	E. Overall Length with Bucket (mm)	123.5" (3137)
	F. Overall Length without Bucket (mm)	95" (2413)
	G. Wheelbase (mm)	36.7" (932)
	H. Dump Reach at Full Height (mm)	25.7" (654)
	I. Bucket Rollback at Ground	28°
	J. Dump Angle	32°
	K. Overall Width (mm)	59" (1499)
	L. Bucket Width (mm)	61.5" (1562)
	M. Clearance Circle - Rear (mm)	50.5" (1283)
	N. Clearance Circle - Front without Bucket (mm)	39.3" (997)
	O. Clearance Circle - Front with Bucket (mm)	73" (1854)
	P. Seat to Ground Height (mm)	34.6" (879)
	Q. Rollback at Full Height	100°
	R. Dump Height (mm)	88.2" (2242)
	S. Departure Angle	24°
	Standard Specification Tire Size	
ENGINE	Make	Yanmar
	Model	4TNV88-Tier III
	Power (kW) @ rpm	47 hp (35) @3000
	Displacement (L)	133.6 cu.in. (2.19)
HYDRAULIC SYSTEM	Auxiliary Hydraulics - Standard (L/min)	18 gpm (68.1)
	Filtration	7 micron
	System Relief Pressure (bar)	2350 psi (162)
	Reservoir Capacity (L)	11.5 gal. (43.5)
CAPACITIES /WEIGHT	Rated Operating Capacity ^A (kg)	1450 lbs. (658)
	With Optional Counterweight ^A (kg)	1550 lbs. (703)
	Tipping Load (kg)	2900 lbs. (1315)
	Fuel Tank (L)	14.3 gal. (54.1)
	Travel Speed - Maximum (km/hr)	6.6 mph (10.6)
	Operating Weight ^B - Approximate (kg)	5623 lbs. (2551)

