

# SKID STEERS

▪ 2056 ▪



[mustangmfg.com](http://mustangmfg.com)

# serious MUSCLE for serious work



- High-reaching radial-lift design reaches heights up to 122 inches with 12.00 tires or 120 inches with 10.00 tires.

- Rated operating capacity of 1,900 pounds, or 2,050 pounds with optional counterweight, make a powerful dent in your workload.



- Powered by a 62-hp Deutz Tier III-certified turbocharged diesel engine, this machine provides extra power when needed.

- The tilt-back ROPS and large engine cover exposes internal components quickly for faster and easier maintenance and service.
- Excellent visibility to the rear tires and an open-front design provides better visibility to the front of the loader.
- Get control with three control options: Joystick, Hand-foot, and dual-hand controls available with standard or high-flow auxiliary hydraulics



West Bend, WI USA  
Tel: 262-334-9461  
Fax: 262-338-7517

For more information on Mustang equipment, call our literature hotline at **800-628-0491** or visit our website: **mustangmfg.com**

A Per SAE J818, SAE J732, and ISO 14397  
B Unit weight with standard bucket, 175 lbs. (79 kg) operator and full fuel tank

## SPECIFICATIONS

	2056	
DIMENSIONS	A. Overall Operating Height - Fully Raised (mm)	160" (4064)
	B. Height to Hinge Pin - Fully Raised (mm)	120.7" (3066)
	C. Overall Height to Top of ROPS (mm)	78.0" (1981)
	D. Ground Clearance to Chassis (mm)	7.5" (191)
	E. Overall Length with Bucket (mm)	126.3" (3208)
	F. Overall Length without Bucket (mm)	94.2" (2393)
	G. Wheelbase (mm)	42" (1067)
	H. Dump Reach at Full Height (mm)	23.1" (587)
	I. Bucket Rollback at Ground	23°
	J. Dump Angle	43°
	K. Overall Width (mm)	62" (1575)
	Overall Width - Narrow Offset Tire Option (mm)	59.7" (1516)
	L. Bucket Width (mm)	60" (1524)
	M. Clearance Circle - Rear (mm)	58" (1473)
	N. Clearance Circle - Front without Bucket (mm)	45" (1143)
	O. Clearance Circle - Front with Bucket (mm)	79" (2006)
	P. Seat to Ground Height (mm)	39.7" (1008)
	Q. Rollback at Full Height	91°
	R. Dump Height (mm)	90" (2066)
S. Departure Angle	25°	
Standard Specification Tire Size	10.00x16.5 HD	
ENGINE	Make	Deutz
	Model	TD2009-Tier III
	Power (kW) @ rpm	62 hp (46) @2500
	Displacement (L)	140 cu.in. (2.3)
	Maximum Torque (Nm) @ rpm	147 ft.-lbs (200) @ 1600
HYDRAULIC SYSTEM	Auxiliary Hydraulics - Standard (L/min)	19 gpm (72)
	High-Flow Hydraulics - Optional (L/min)	30 gpm (114)
	Filtration	4 micron
	System Relief Pressure (bar)	2750 psi (190)
	Reservoir Capacity (L)	12 gal. (45)
CAPACITIES/WEIGHT	Rated Operating Capacity <sup>A</sup> (kg)	1900 lbs. (862)
	With Optional Counterweight <sup>A</sup> (kg)	2050 lbs. (930)
	Tipping Load (kg)	3800 lbs. (1724)
	Fuel Tank (L)	16 gal. (60)
	Travel Speed - Maximum (km/hr)	12.4 mph (20)
	Operating Weight <sup>B</sup> - Approximate (kg)	6800 lbs. (3084)

