

SKID STEERS

■ 2086 ■



mustangmfg.com

serious MUSCLE for serious work



- Increased operating capacity of up to 2,900 pounds (with optional counterweight) add strength to your compact fleet.

- Wider tread width, low center of gravity, and increased machine width provide superior stability.



- Optional hydraulic Multi-Tach™ attachment system allows the operator to change attachments without leaving the seat.

- Safety system disables lift, tilt, drive and auxiliary hydraulic functions when the operator raises the seat bar, leaves the seat or turns off the ignition.
- Sturdy Level II-certified ROPS/FOPS structure provides protection, yet allows an unobstructed view to the attachment and surrounding work areas.



West Bend, WI USA
Tel: 262-334-9461
Fax: 262-338-7517

For more information on
Mustang equipment, call our
literature hotline at
800-628-0491
or visit our website:
mustangmfg.com

A Per SAE J818, SAE J732, and ISO 14397
B Unit weight with standard bucket, 175 lbs.
(79 kg) operator and full fuel tank

SPECIFICATIONS

	2086	
DIMENSIONS	A. Overall Operating Height - Fully Raised (mm)	168.3" (4275)
	B. Height to Hinge Pin - Fully Raised (mm)	123" (3124)
	C. Overall Height to Top of ROPS (mm)	81" (2057)
	D. Ground Clearance to Chassis (mm)	8.0" (203)
	E. Overall Length with Bucket (mm)	140.3" (3563)
	F. Overall Length without Bucket (mm)	105.8" (2687)
	G. Wheelbase (mm)	48.4" (1229)
	H. Dump Reach at Full Height (mm)	35.2" (894)
	I. Bucket Rollback at Ground	28°
	J. Dump Angle	37°
	K. Overall Width (mm)	69" (1753)
	L. Bucket Width (mm)	74" (1880)
	M. Clearance Circle - Rear (mm)	69" (1679)
	N. Clearance Circle - Front without Bucket (mm)	54" (1372)
	O. Clearance Circle - Front with Bucket (mm)	90" (2299)
	P. Seat to Ground Height (mm)	42" (1067)
	Q. Rollback at Full Height	84°
	R. Dump Height (mm)	92.7" (2354)
	S. Departure Angle	26°
Standard Specification Tire Size	12.00x16.5 HD	
ENGINE	Make	Yanmar
	Model	4TNV98T-Tier III
	Power (kW) @ rpm	84 hp (62.6) @ 2500
	Displacement (L)	202 cu.in. (3.3)
	Maximum Torque (Nm) @ rpm	222 ft.-lbs (301) @ 1850
HYDRAULIC SYSTEM	Auxiliary Hydraulics - Standard (L/min)	21.8 gpm (82.3)
	High-Flow Hydraulics - Optional (L/min)	36.9 gpm (139.6)
	Filtration	4 micron
	System Relief Pressure (bar)	3000 psi (207)
	Reservoir Capacity (L)	16 gal. (60)
CAPACITIES /WEIGHT	Rated Operating Capacity ^A (kg)	2600 lbs. (1179)
	With Optional Counterweight ^A (kg)	2900 lbs. (1315)
	Tipping Load (kg)	5200 lbs. (2358)
	Fuel Tank (L)	24 gal. (91)
	Travel Speed - Maximum (km/hr)	12.3 mph (19.8)
	Operating Weight ^B - Approximate (kg)	7900 lbs. (3583)

