

# SKID STEERS

■ 2700V ■



[mustangmfg.com](http://mustangmfg.com)

# time to get some VERTICAL FORCE



- All-new vertical-lift design delivers extended reach and 130-inch lift height, higher than any competitor in its weight class.

- Powered by an 84-hp, turbocharged diesel engine with 215 ft.-lbs. of torque, this workhorse has a rated operating capacity of 2,700 lbs. for the toughest jobs.



- Domed, wide-view glass door option reduces glare and provides optimal visibility to the lift arm, attachment and front work area.

- Side-folding restraint bar and adjustable armrests enhance comfort and safety.
- Pilot-operated joystick controls with adjustable handles, or pilot-operated hand/foot controls.



West Bend, WI USA  
Tel: 262-334-9461  
Fax: 262-338-7517

For more information on Mustang equipment, call our literature hotline at **800-628-0491** or visit our website: **mustangmfg.com**

A Per SAE J818, SAE J732, and ISO 14397  
B Unit weight with standard bucket, 175 lbs. (79 kg) operator and full fuel tank

## SPECIFICATIONS

		2700V	
DIMENSIONS	A.	Overall Operating Height - Fully Raised (mm)	169.8" (4313)
	B.	Height to Hinge Pin - Fully Raised (mm)	130.3" (3310)
	C.	Overall Height to Top of ROPS (mm)	80.5" (2045)
	D.	Ground Clearance to Chassis (mm)	8.0" (203)
	E.	Overall Length with Bucket (mm)	149.2" (3790)
	F.	Overall Length without Bucket (mm)	115" (2921)
	G.	Wheelbase (mm)	49.8" (1265)
	H.	Dump Reach at Full Height (mm)	35" (864)
	I.	Bucket Rollback at Ground	28°
	J.	Dump Angle	41°
	K.	Overall Width (mm)	69.5" (1765)
	L.	Bucket Width (mm)	70" (1778)
	M.	Clearance Circle - Rear (mm)	65.5" (1664)
	N.	Clearance Circle - Front without Bucket (mm)	74.6" (1895)
	O.	Clearance Circle - Front with Bucket (mm)	93" (2362)
	P.	Seat to Ground Height (mm)	40.2" (1021)
	Q.	Rollback at Full Height	94°
R.	Dump Height (mm)	99" (2515)	
S.	Departure Angle	27°	
	Standard Specification Tire Size	12.00x16.5 HD	
ENGINE	Make	Yanmar	
	Model	4TNV98T-Tier III	
	Power (kW) @ rpm	84 hp (62.6) @ 2500	
	Displacement (L)	202 cu.in. (3.3)	
	Maximum Torque (Nm) @ rpm	222 ft.-lbs (301) @ 1850	
HYDRAULIC SYSTEM	Auxiliary Hydraulics - Standard (L/min)	21.8 gpm (82.5)	
	High-Flow Hydraulics - Optional (L/min)	36.9 gpm (139.7)	
	Filtration	4 micron	
	System Relief Pressure (bar)	3300 psi (207)	
	Reservoir Capacity (L)	11 gal. (41.6)	
CAPACITIES /WEIGHT	Rated Operating Capacity <sup>A</sup> (kg)	2700 lbs. (1225)	
	With Optional Counterweight <sup>A</sup> (kg)	3000 lbs. (1361)	
	Tipping Load (kg)	5400 lbs. (2449)	
	Fuel Tank (L)	22 gal. (83.3)	
	Travel Speed - Maximum (km/hr)	11.9 mph (19.2)	
	Operating Weight <sup>B</sup> - Approximate (kg)	8000 lbs. (3629)	

### REFERENCE DIAGRAMS

