

# TELEHANDLERS

■ 519 ■



[mustangmfg.com](http://mustangmfg.com)

# CONQUER confined spaces



- Operator has full 360° visibility from the cab for increased safety.

- Two-speed transmission provides travel speeds up to 15 mph and a lower speed for enhanced tractive power.



- Double-wall rear tower and heavy-duty boom nose provide extra support for increased longevity.

- Auxiliary hydraulic flow up to 22 gpm provide excellent hydraulic performance to power a variety of attachments.
- ROPS/FOPS canopy is standard; a ROPS/FOPS cab is optional.
- Engine accessibility is made simple with a large, hinged hood on the side of the machine that opens wide to allow plenty of room to access maintenance points.



West Bend, WI USA  
Tel: 262-334-9461  
Fax: 262-338-7517

For more information on Mustang equipment, call our literature hotline at **800-628-0491** or visit our website: **mustangmfg.com**

## SPECIFICATIONS

		519
CAPACITIES	Lift Capacity (kg)	5500 lbs. (2495)
	Maximum Lift Height (m)	19'1" (5.8)
	Capacity at Maximum Lift Height (kg)	3,000 lbs. (1180)
	Maximum Forward Reach (m)	10'10" (3.3)
	Capacity at Maximum Forward Reach (kg)	1850 lbs.
	Maximum Reach Below Grade (mm)	0" (0)
ENGINE	Manufacturer	Deutz
	Power (kW)	64 hp (48)
	Aspiration	Turbocharged
	Model	TD2009 L04
	Rated Speed	2750
COMPONENTS	Transmission	Rexroth 2-speed
	Maximum Travel Speed	15 mph (24)
	Selective Steering	4-wheel 2-wheel Crab
	Brakes	Internal Wet Disc 2-wheel Hydraulic
	Parking Brake	SAHR
	Axle Manufacturer	Dana
HYDRAULIC SYSTEM	Pump Type	Gear
	Total Capacity (L/min.)	22 gpm (83)
	System Pressure (bar)	3350 psi (231)
	Hydraulic Tank Capacity (L)	18 gal. (68)
GENERAL SPECIFICATIONS	Approximate Weight (kg)	10,000 lbs. (4536)
	Length - Less Forks (m)	12'4" (3.76)
	Width (m)	5'11" (1.80)
	Ground Clearance (mm)	14" (350)
	Wheelbase (m)	7'6" (2.29)
	Turning Radius (m)	11' (3.35)
	Overall Height (m)	6'4" (1.93)
	Frame Leveling	N/A
	Fuel Capacity (L)	17 gal. (64)
TIRE OPTIONS	12.00 x 16.5 Bias/10PR	
	12.00 x 16.5 Bias/10PR Foam Filled	
	Solid-Fill	

### LOAD CHART

- A** 5,500 lbs.
- B** 4,000 lbs.
- C** 3,000 lbs.
- D** 2,000 lbs.
- E** 1,850 lbs.

